







The CL400 with the 14 buttons a total of 8,191 different codes are available, any of which may be entered in any order. For use on internal and external doors. With existing Mortice latch or lock, the existing lock must have 22mm fixing hole below the follower (spindle).

Technical Specifications

Functions: 7 available

Spindle Type: 2 part 8mm (5/16") spring loaded spindle

Material: Zinc alloy

Door thickness:35mm - 65mm (13/8" - 21/2")Door material:Suitable for wooden doorsButtons:14 stainless steel buttons

Non handed: Locks will fit doors hung on the left or right

Fitting: Easy fit Fitting Options: Vertical

Finish: Stainless steel and polished brass Codes: 8, 191 non sequential codes available

Code storage: Single code

Key override: Yes. Keyed alike can be ordered

Functions:

Models: 400, 405, 410, 415, 420, 425

Mortice Latch: 420 & 425 Medium duty, stainless steel latchbolt head

with "anti" shim deadlocking plunger, 8mm (5/16") follower

60mm (23/8") backset, requires 25mm (1") hole,

82mm (31/4") deep 70mm (23/4") backset, requires 25mm (1") hole,

92mm (35/16") deep

410 outside lever will retract latch after correct code

415 as 410 with Code Free option.

Mortice Lock: Euro profile mortice sash lock with deadbolt

and latchbolt. Supplied with double euro profile cylinders with three keys. May be ordered keyed alike

Code Free access option via keypad on models

405, 415 & 425

Full Mortice Lock: Safety feature. 420 prevents accidental lock in


425 as 420 with Code Free function on keypad


Back to back: 410 (Mortice Latch) may be ordered with two code

plates to provide coded access in both directions 400 Front and back plates only. 405 as 400 with Code Free

CL410 CL415 41mm (1¹/₁₀)

External Dimensions:





Code change method:

Requires removal of lock from door

Use in offices / schools / warehouses / hospitals / care homes / nurseries / hotels / leisure facilities / the home.

